



TURKEY DERBY XLIX

LIMITED LATE MODEL DIVISION

R U L E B O O K

THE RULES BELOW ARE THE GENERAL GUIDELINES FOR ALL CARS
THAT COMPETE IN THIS DIVISION AT TURKEY DERBY 2022.

IF THESE RULES DO NOT CLEARLY SAY THAT SOMETHING IS LEGAL, ASSUME THAT IT IS NOT PERMITTED.

WALL OFFICIALS RESERVE THE RIGHT TO ADJUST OR AMEND THE RULES IN THE BEST INTEREST OF SAFETY AND/OR COMPETITION.

TECH QUESTIONS? Call Rob Hyer at (732) 824-4507

REQUIRED SAFETY EQUIPMENT

- The use of a HANS DEVICE or Hans-like device is MANDATORY. 5 year expiration.
- Window net MANDATORY.
- 5-point Harness MANDATORY. SFI 38.1 Belts good for 2 years.
- Full face Helmets are MANDATORY. Must have Snell SA 15 or newer sticker. NO motorcycle M Helmets.
- Driver must wear a one piece fire suit and flame retardant underwear. Both must be in good condition, no rips or holes! SFI 5. Driving gloves and driving shoes required.
- Full containment seat MANDATORY.
- Fire Extinguisher MANDATORY. Unused and fully charged at all times.
- Seat Belts expire 2 years from manufacture date. Make sure you are current!
- All other New Jersey State Safety Regulations MUST BE STRICTLY ADHERED TO.

RACECEIVER FREQUENCY 467.8125

ALL CARS MUST PASS A GENERAL SAFETY AND TECH INSPECTION BEFORE GOING OUT FOR PRACTICE.

MINIMUM TOTAL WEIGHT FOR ALL CARS:

604 Crate Motor 2,800 pounds plus weight penalties

11:1 Compression 2,900 pounds plus weight penalties

ALL CARS: Maximum Left Side percentage – 58%

NO TRACTION CONTROL OF ANY KIND. WEIGHT AND FRAME HEIGHTS CHECKED BEFORE THE RACE.

Exceptions and Additions

MOTORS MUST MEET 2022 WALL STADIUM SPEEDWAY LIMITED LATE MODEL RULES.

If different, you **MUST** declare differences and get a weight penalty **BEFORE** practice.

Weight Penalty as listed: Base compression ratio 11:1

- **Cubic Inches:**

- **1 cubic inch over 358 = 6.8 pounds**

Compression and Cubic Inch penalties to be added **before** coming to the track.

Compression Ratio, Cubic Inches and Weight must be displayed on the hood – 3" high on the right side.

- 4412 carburetor allowed
- 7 ¼" clutch
- All cars must run Hoosier 1057 L and 1057 R tires. Available for purchase at the track.
- 604 must run 650 CFM Carburetor ONLY.
- Ride height 4"
- Maximum tread width 80"
- Wheel width 10"
- Lead weight added must not be lower than the side frame rails and must be positioned within the wheel base.

QUESTIONS about the event? Call Wall Stadium Speedway at 732-681-6400 or email wallstadiumspeedway@gmail.com